


White PVC 120 Crescent Top

Phone (503) 289-7720 Fax (503) 289-8920 Toll Free (800) 234-2358

Application: This FDA/USDA compliant belt is an industry favorite. Conveyorbelt's crescent profile is very popular for use in general-purpose incline applications. The durable all polyester interwoven carcass provides low stretch, excellent fastener retention and good tear resistance. The economical PVC cover compound has superior mineral oil resistance as well as excellent wear characteristics.



Technical Data

	Imperial
Working Tension	120
Number Of Plies	1
Fabric Type	Spun Poly
Top Surface	Crescent
Bottom Surface	Brushed
Overall Gauge	1/4"
Weight (Per Inch of Width)	.091
Bottom Coefficient	0.25 (approx.)
Minimum Rec. Pulley Diameters	3.0 in.
Elongation At Rated Tension	< 2%
Working Temperature	20 to 180 F

Splicing Methods

FOF	Finger	Bias Stepped	Skived Bias	Clipper *	Alligator *	Staple *
No	Yes	No	Yes	1 or UX1	15	125

* Fastener manufacturer should be consulted to review belt and application information.

No warranty, including implied warranty of merchantability, fitness for a particular purpose, or other warranty of quality is either expressed or implied of this product. The information on this specification sheet supercedes all previously printed material.