

## Black 330 MOR V-Cleat

Phone (503) 289-7720 Fax (503) 289-8920 Toll Free (800) 234-2358

---

### Application:

**FREE-FLOWING MATERIALS:** V-Cleat belting is designed to handle the aggressive transfer and elevation of materials like coal, potash, stone, gravel, bark and wood chips. A chevron-top design locks free-flowing materials to the belt surface when the incline exceeds the capabilities of standard smooth belting. This prevents "slip-back" and the costly production losses that go with it. Bare back has the lowest coefficient of friction, for slider bed applications.

**CLEATS** - The chevron cleats are an integral part of the original manufactured belt. Cleats are a full 1/4" high, with straight sides and a 3/8" base. With a 6" span, the chevrons repeat continuously across the width of the belt, overlapping from row to row to maintain a smooth running surface on the return idlers. For wet applications, the belt can be reversed to allow water to drain off the cleats while the load moves up the incline. V-cleat belt is normally available in 2 and 3 ply carcass constructions can be manufactured with and carcass. Special widths include 36" through 72".

### Technical Data

	<b>Imperial</b>
<b>Working Tension</b>	330
<b>Number Of Plies</b>	3
<b>Fabric Type</b>	Poly/Nylon
<b>Top Surface</b>	1/8"
<b>Bottom Surface</b>	Bare
<b>Overall Gauge</b>	5/16"
<b>Weight (Per Inch of Width)</b>	.240
<b>Minimum Rec. Pulley Diameters</b>	12"
<b>Working Temperature</b>	-30/200 F

### Splicing Methods

<b>Vulcanized</b>	<b>Plate</b>	<b>Hinged</b>	<b>Hinged</b>
Bias	140/190	375, 550	R5

\* Fastener manufacturer should be consulted to review belt and application information.

No warranty, including implied warranty of merchantability, fitness for a particular purpose, or other warranty of quality is either expressed or implied of this product. The information on this specification sheet supercedes all previously printed material.